

MSZ-S SERIES

MSZ-G SERIES


Introducing a compact and stylish indoor unit with amazingly quiet performance. Not only are neat installations in small bedrooms possible, increase energy-savings by selecting the optimal capacity required for each room.



"Rank A++/A+" Energy Savings Achieved for Entire Range of Series



All models in the series, from the low-capacity 25 to the high-capacity 71, have achieved the "Rank A++" for SEER and "Rank A+" for SCOP as energy-savings rating. For home use, such as in bedrooms and living rooms, to light commercial use, such as in offices, our air conditioners are contributing to reduced energy consumption in a wide range.




Wide Line-up

Eight different indoor units (Model 15-71) are available to meet your diversified air conditioning needs.



MSZ-SF15 / 20VA*
*for MXZ connection



MSZ-SF25 / 35 / 42 / 50VE3



MSZ-GF60 / 71VE2

Compact and Stylish

(MSZ-SF15/20VA)

The stylish, square indoor unit adds a touch of class to any room interior. The compact design is 64mm thinner than our previous indoor unit with the lowest output capacity (MSZ-GE22VA).

Comparison with our previous model GE



Family Design

(MSZ-SF15/20/25/35/42/50)

Models in the 25-50 class are introduced as single-split units while retaining the popular design of the SF15/20VA* as indoor units exclusively for multi-systems. From small rooms to living rooms, it is possible to coordinate residences with a unified design.

*Size may vary.



“Weekly Timer”



Easily set desired temperatures and operation start/stop times to match lifestyle patterns. Reduce wasted energy consumption by using the timer to prevent forgetting to turn off the unit and eliminate temperature setting adjustments.

■ Example Operation Pattern (Winter/Heating mode)

	Mon.	Tues.	Wed.	Thurs.	Fri.	Sat.	Sun.
6:00	ON 20°C	ON 20°C	ON 20°C	ON 20°C	ON 20°C	ON 20°C	ON 20°C
8:00	Automatically changes to high-power operation at wake-up time						
10:00	OFF	OFF	OFF	OFF	OFF	ON 18°C	ON 18°C
12:00	Automatically turned off during work hours						Midday is warmer, so the temperature is set lower
14:00							
16:00							
18:00	ON 20°C	ON 20°C	ON 20°C	ON 20°C	ON 20°C	ON 20°C	ON 20°C
20:00	Automatically turns on, synchronized with arrival at home						Automatically raises temperature setting to match time when outside-air temperature is low
22:00							
(during sleeping hours)	ON 18°C	ON 18°C	ON 18°C	ON 18°C	ON 18°C	ON 18°C	ON 18°C
	Automatically lowers temperature at bedtime for energy-saving operation at night						

Settings


Pattern Settings: Input up to four settings for each day

Settings: • Start/Stop operation • Temperature setting *The operation mode cannot be set.

■ Easy set-up using dedicated buttons




The remote controller is equipped with buttons that are used exclusively for setting the Weekly Timer. Setting operation patterns is easy and quick.



- Start by pushing the “SET” button and follow the instructions to set the desired patterns. Once all of the desired patterns are input, point the top end of the remote controller at the indoor unit and push the “SET” button one more time. (Push the “SET” button only after inputting all of the desired patterns into the remote controller memory. Pushing the “CANCEL” button will end the set-up process without sending the operation patterns to the indoor unit).
- It takes a few seconds to transmit the Weekly Timer operation patterns to the indoor unit. Please continue to point the remote controller at the indoor unit until all data has been sent.
- When “Weekly Timer” is set, temperature can not be set 10°C.

Low Standby Power

Electrical devices consume standby power even when they are not in actual use. While we obviously strive to reduce power consumption during actual use, reducing this wasted power that cannot be seen is also very important.




Air Purifying Filter

(MSZ-SF25/35/42/50, MSZ-GF60/71)

This filter generates stable antibacterial and deodourising effects. The size of the three-dimensional surface has been increased as well, enlarging the filter capture area. These features give the Air Purifying Filter better dust collection performance than conventional filters. The superior air-cleaning effectiveness raises room comfort yet another level.



* It is okay to wash the filter with water (air-cleaning effect is maintained)




3D surface (Waved surface)

“i save” Mode



“i save” is a simplified setting function that recalls the preferred (preset) temperature by pressing a single button on the remote controller. Press the same button twice in repetition to immediately return to the previous temperature setting. Using this function contributes to comfortable, waste-free operation, realising the most suitable air conditioning settings and saving on power consumption when, for example, leaving the room or going to bed.



* Temperature can be preset to 10°C when heating in the “i-save” mode.

Outdoor Units for Cold Region (25/35/42/50)

Single split-type outdoor units are available in both standard and heater-equipped units. An electric heater is installed in each unit to prevent freezing in cold outdoor environments.



MUZ-SF25/35/42VE

MUZ-SF50VE

MUZ-SF25/35/42VEH

MUZ-SF50VEH

MSZ-S SERIES



Indoor Unit



MSZ-SF15/20VA



Outdoor Unit

For MXZ Connection Only

Remote Controller



Type		Inverter Heat Pump					
Indoor Unit		MSZ-SF15VA	MSZ-SF20VA	MSZ-SF25VE3	MSZ-SF25VE3	MSZ-SF35VE3	MSZ-SF35VE3
Outdoor Unit		for MXZ connection		MUZ-SF25VE	MUZ-SF25VEH	MUZ-SF35VE	MUZ-SF35VEH
Refrigerant		R410A ⁽¹⁾					
Power Supply		Outdoor Power supply					
Source		230/Single/50					
Outdoor (V / Phase / Hz)							
Cooling	Design load	kW	-	-	2.5	2.5	3.5
	Annual electricity consumption ⁽²⁾	kWh/a	-	-	116	116	171
	SEER ⁽⁴⁾		-	-	7.6	7.6	7.2
	Energy efficiency class		-	-	A++	A++	A++
	Capacity	kW	-	-	2.5	2.5	3.5
	Min-Max	kW	-	-	0.9-3.4	0.9-3.4	1.1-3.8
Heating (Average Season) ⁽⁵⁾	Total Input	Rated	kW	-	0.600	0.600	1.080
	Design load	kW	-	-	2.4(-10°C)	2.4(-10°C)	2.9(-10°C)
	Declared Capacity	at reference design temperature	kW	-	2.4(-10°C)	2.4(-10°C)	2.9(-10°C)
		at bivalent temperature	kW	-	2.4(-10°C)	2.4(-10°C)	2.9(-10°C)
		at operation limit temperature	kW	-	2.0(-15°C)	2.2(-15°C)	1.6(-20°C)
	Back up heating capacity	kW	-	-	0.0(-10°C)	0.0(-10°C)	0.0(-10°C)
Indoor Unit	Annual electricity consumption ⁽²⁾	kWh/a	-	-	764	790	948
	SCOP ⁽⁴⁾		-	-	4.4	4.3	4.3
	Energy efficiency class		-	-	A+	A+	A+
	Capacity	Rated	kW	-	3.2	3.2	4.0
	Min-Max	kW	-	-	1.0-4.1	1.0-4.1	1.3-4.6
	Total Input	Rated	kW	-	0.780	0.780	1.030
Outdoor Unit	Operating Current (Max)	A	-	-	8.4	8.5	8.5
	Input	Rated	kW	0.017	0.019	0.024	0.027
	Operating Current(Max)	A	-	-	0.2	0.2	0.3
	Dimensions	H*W*D	mm	250-760-168	250-760-168	299-798-195	299-798-195
	Weight	kg	-	-	10	10	10
	Air Volume (SL-Lo-Mid-Hi-SH ⁽³⁾) (Dry/Wet)	m³/min	3.5 - 3.9 - 4.6 - 5.5 - 6.4	3.5 - 3.9 - 4.6 - 5.5 - 6.9	3.2 - 4.1 - 5.6 - 7.2 - 9.1	3.2 - 4.1 - 5.6 - 7.2 - 9.1	3.2 - 4.1 - 5.6 - 7.2 - 9.1
Ext. Piping	Sound Level (SPL)	dB(A)	21 - 26 - 30 - 35 - 40	21 - 26 - 30 - 35 - 42	19 ⁽⁶⁾ - 24 - 30 - 36 - 42	19 ⁽⁶⁾ - 24 - 30 - 36 - 42	19 ⁽⁶⁾ - 24 - 30 - 36 - 42
	Sound Level (PWL)	dB(A)	59	60	57	57	57
	Dimensions	H*W*D	mm	-	550-800-285	550-800-285	550-800-285
	Weight	kg	-	-	31	31	31
	Air Volume	m³/min	-	-	31.1	31.1	35.9
	Sound Level (SPL)	dB(A)	-	-	30.7	30.7	35.9
Guaranteed Operating Range (Outdoor)	Sound Level (PWL)	dB(A)	-	-	47	49	49
	Operating Current (Max)	A	-	-	58	58	62
	Breaker Size	A	-	-	8.2	8.2	8.2
	Diameter	Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52
	Max.Length	Out-In	m	-	20	20	20
	Max.Height	Out-In	m	-	12	12	12

(1) Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.
The GWP of R410A is 2088 in the IPCC 4th Assessment Report.

(2) Energy consumption based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

(3) SH: Super High

(4) SEER, SCOP and other related description are based on COMMISSION DELEGATED REGULATION (EU) No.626/2011. The temperature conditions for calculating SCOP are based on "Average Season".


(5) Please see page 63 for heating (warmer season) specifications.

(6) For single use: only 19dB(A). For multi use (MXZ): 21dB(A).

MSZ-S SERIES MSZ-G SERIES



Indoor Unit



MSZ-SF25/35/42/50VE3



MSZ-GF60/71VE2

Outdoor Unit



MUZ-SF25/35/42VE(H)



MUZ-SF50VE(H)
MUZ-GF60/71VE

Remote Controller



Type			Inverter Heat Pump					
Indoor Unit			MSZ-SF42VE3	MSZ-SF42VE3	MSZ-SF50VE3	MSZ-SF50VE3	MSZ-GF60VE2	MSZ-GF71VE2
Outdoor Unit			MUZ-SF42VE	MUZ-SF42VEH	MUZ-SF50VE	MUZ-SF50VEH	MUZ-GF60VE	MUZ-GF71VE
Refrigerant			R410A ⁽¹⁾					
Power Supply			Outdoor Power supply					
Source			230/Single/50					
Outdoor (V / Phase / Hz)								
Cooling	Design load	kW	4.2	4.2	5	5	6.1	7.1
	Annual electricity consumption ⁽²⁾	kWh/a	196	196	246	246	311	364
	SEER ⁽³⁾		7.5	7.5	7.2	7.2	6.8	6.8
	Energy efficiency class		A++	A++	A++	A++	A++	A++
	Capacity							
Heating (Average Season) ⁽⁴⁾	Rated	kW	4.2	4.2	5	5	6.1	7.1
	Min-Max	kW	0.8-4.5	0.8-4.5	1.4-5.4	1.4-5.4	1.4-7.5	2.0-8.7
	Total Input	Rated	kW	1.340	1.340	1.660	1.660	1.790
	Design load	kW	3.8 (-10°C)	3.8 (-10°C)	4.2 (-10°C)	4.2 (-10°C)	4.6 (-10°C)	6.7 (-10°C)
	Declared Capacity							
Heating (Average Season) ⁽⁴⁾	at reference design temperature	kW	3.8 (-10°C)	3.8 (-10°C)	4.2 (-10°C)	4.2 (-10°C)	4.6 (-10°C)	6.7 (-10°C)
	at bivalent temperature	kW	3.8 (-10°C)	3.8 (-10°C)	4.2 (-10°C)	4.2 (-10°C)	4.6 (-10°C)	6.7 (-10°C)
	at operation limit temperature	kW	3.4 (-15°C)	2.2 (-20°C)	3.4 (-15°C)	2.3 (-20°C)	3.7 (-15°C)	5.4 (-15°C)
	Back up heating capacity	kW	0.0 (-10°C)	0.0 (-10°C)	0.0 (-10°C)	0.0 (-10°C)	0.0 (-10°C)	0.0 (-10°C)
	Annual electricity consumption ⁽²⁾	kWh/a	1215	1242	1351	1380	1489	2204
Cooling	SEER ⁽³⁾		4.4	4.3	4.4	4.3	4.3	4.2
	Energy efficiency class		A+	A+	A+	A+	A+	A+
	Capacity							
	Rated	kW	5.4	5.4	5.8	5.8	6.8	8.1
	Min-Max	kW	1.3-6.0	1.3-6.0	1.4-7.3	1.4-7.3	2.0-9.3	2.2-9.9
Heating (Average Season) ⁽⁴⁾	Total Input	Rated	kW	1.580	1.58	1.7	1.7	2.23
	Operating Current (Max)	A	9.5	9.5	12.3	12.3	14.5	16.6
	Input	Rated	kW	0.027	0.027	0.035	0.035	0.058
	Operating Current(Max)	A	0.3	0.3	0.3	0.3	0.5	0.5
	Dimensions	H*W*D	mm	299-798-195	299-798-195	299-798-195	299-798-195	325-1100-238
Indoor Unit	Weight	kg	10	10	10	10	16	16
	Air Volume (SL-Lo-Mid-Hi-SH ⁽⁵⁾ Dry/Wet)	m³/min	4.7 - 5.8 - 6.7 - 7.9 - 9.1	4.7 - 5.8 - 6.7 - 7.9 - 9.1	5.1 - 6.2 - 7.0 - 8.2 - 9.9	5.1 - 6.2 - 7.0 - 8.2 - 9.9	9.8-11.3-13.4-15.6-18.3	9.7-11.5-13.3-15.4-17.8
	Heating	m³/min	4.7 - 5.8 - 7.2 - 9.1 - 11.4	4.7 - 5.8 - 7.2 - 9.1 - 11.4	5.1 - 6.4 - 8.0 - 9.8 - 12.0	5.1 - 6.4 - 8.0 - 9.8 - 12.0	9.8-11.3-13.4-15.6-18.3	10.2-11.5-13.3-15.4-17.8
	Sound Level (SPL)	dB(A)	26 ⁽⁶⁾ - 31 - 34 - 38 - 42	26 ⁽⁶⁾ - 31 - 34 - 38 - 42	28 ⁽⁷⁾ - 33 - 36 - 40 - 45	28 ⁽⁷⁾ - 33 - 36 - 40 - 45	29 - 37 - 41 - 45 - 49	30 - 37 - 41 - 45 - 49
	Heating	dB(A)	26 ⁽⁶⁾ - 31 - 36 - 42 - 47	26 ⁽⁶⁾ - 31 - 36 - 42 - 47	28 ⁽⁷⁾ - 33 - 38 - 43 - 49	28 ⁽⁷⁾ - 33 - 38 - 43 - 49	29 - 37 - 41 - 45 - 49	30 - 37 - 41 - 45 - 49
Outdoor Unit	Sound Level (PWL)	dB(A)	57	57	58	58	65	65
	Dimensions	H*W*D	mm	550-800-285	550-800-285	880-840-330	880-840-330	880-840-330
	Weight	kg	35	35	55	55	50	53
	Air Volume							
	Cooling	m³/min	35.2	35.2	44.6	44.6	49.2	50.1
Indoor Unit	Heating	m³/min	33.6	33.6	44.6	44.6	49.2	48.2
	Sound Level (SPL)	dB(A)	50	50	52	52	55	55
	Heating	dB(A)	51	51	52	52	55	55
	Sound Level (PWL)	dB(A)	63	63	65	65	65	65
	Operating Current (Max)	A	9.2	9.2	12	12	14	16.1
Ext. Piping	Breaker Size	A	10	10	16	16	20	20
	Diameter	Liquid/Gas	mm	6.35 / 9.52	6.35 / 9.52	6.35 / 12.7	6.35 / 12.7	6.35/15.88
	Max.Length	Out-In	m	20	20	30	30	30
	Out-In	m	12	12	15	15	15	15
	Max.Height	Out-In	m	12	12	15	15	15
Guaranteed Operating Range (Outdoor)	Cooling	°C	-10 ~ +46	-10 ~ +46	-10 ~ +46	-10 ~ +46	-10 ~ +46	-10 ~ +46
	Heating	°C	-15 ~ +24	-20 ~ +24	-15 ~ +24	-20 ~ +24	-15 ~ +24	-15 ~ +24

(1) Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

The GWP of R410A is 2088 in the IPCC 4th Assessment Report.

(2) Energy consumption based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

(3) SH: Super High

(4) SEER, SCOP and other related description are based on COMMISSION DELEGATED REGULATION (EU) No.626/2011. The temperature conditions for calculating SCOP are based on "Average Season".

(5) Please see page 63 for heating (warmer season) specifications.

(6) For single use: only 26dB(A). For multi use (MX2): 28dB(A).

(7) For single use: only 28dB(A). For multi use (MX2): 30dB(A).